



XT 3.78 C5

PORTABLE POWER

WATERPUMP Range AQUALINE SPECIALIST

PRODUCT ADVANTAGES

HONDA Professional Engine
Easy access to the turbine (without tools)
Automatic priming
Resistant pump-barrel
Offers accessories

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range AQUALINE SPECIALIST

High performance under extreme conditions.



GENERAL SPECIFICATIONS

Range	AQUALINE SPECIALIST
Type liquid	Extremely heavily sedimented water pump
Suction diameter [mm]	76
Backflow diameter (mm)	76
Outflow maximum (L/min)	1340
Outflow maximum (m3/h)	80,4
Lifting height (m)	27
Suction height (m)	8
Granulometry (mm)	27
Automatic priming	Oui
Fuel	Petrol
Tank (L)	5,3
75% cons. (l/h)	2
75% Autonomy (h)	2,7
Sound power level guaranteed LwA dB(A)	110
Acoustic pressure level @1m in dB(A)	94
Acoustic pressure level @7m in dB(A)	80

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX240_C5
Engine Type	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	242
Oil system capacity including filters (l)	1,1

DIMENSIONS AND WEIGHT

Length (cm)	69
Width (cm)	48,5
Height (cm)	53,2
Dry Weight (kg)	58

PACKAGING

Packaging type	Box
Length (cm)	72
Width (cm)	52
Height (cm)	58
Weight (kg)	68,5
Pallet type	120/80
Number of box by pallet	4
Pallet height (cm)	129
weight of the packaged Pallet (kg)	284

ACCESSORIES SUPPLIED

Inlet filter
Circlips
Screw-on connectors
User and maintenance manual

OPTIONS

- RHO** RHO - Protective cover for HX 3000 / HXC 3000 / PERFORM 3000 - 3000 XL / PRESTIGE 3000 / ST 2,36 - 3,60 / TR 2,36 - 3,60 / HP 2,26 / XT 3,78 ; Dimensions : 70 x 45 x 50 cm
- R12** R12 - Piping kit for 3 water pumps made up of 5 m suction + 25 m lift
- R14** R14 - Rapid connections kit for 3 water pumps