



## HP 2.26 C5

PORTABLE POWER

WATERPUMP Range AQUALINE SPECIALIST

### PRODUCT ADVANTAGES

- HONDA Professional Engine
- Automatic priming
- Solid and high-performance equipment
- Offeres accessories
- High-pressure equipment

With nearly 6 bar of pressure, the HP 2.26 H can be used for high-pressure cleaning of machinery, such as agricultural vehicles. When combined with the nozzle kit, it can be used to suppress fires.

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

### Range AQUALINE SPECIALIST

High performance under extreme conditions.



## HP 2.26 C5

### WATER PUMP SPECIFICATIONS

Range	AQUALINE SPECIALIST
Type liquid	High voltage use
Suction diameter [mm]	50
Backflow diameter (mm)	50
Outflow maximum (L/min)	440
Outflow maximum (m3/h)	26,40
Lifting height (m)	57
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Yes
Fuel	Petrol
Tank (L)	3,10
75% cons. (l/h) *	0,90
75% Autonomy (h) *	3,40
Sound power level guaranteed LwA dB(A)	108
Acoustic pressure level @1m in dB(A)	92
Acoustic pressure level @7m in dB(A)	77

### ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX160_C5
Distribution	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	163
Oil system capacity including filters (l)	0,60

### DIMENSIONS AND WEIGHT

Length (cm)	41,50
Width (cm)	54,50
Height (cm)	45,50
Dry Weight (kg)	30

### PACKAGING

Packaging type	Box
Length (cm)	54
Width (cm)	42
Height (cm)	45
Weight (kg)	35
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	148
weight of the packaged Pallet (kg)	430

### ACCESSORIES SUPPLIED



Inlet filter
Screw-on connectors



Circlips
User and maintenance manual



### OPTIONS



<b>RBH1</b>	Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)
<b>RBH0-5</b>	Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).
<b>RHO</b>	Cover for SDMO 's generating sets, welding sets and water pumps
<b>R09</b>	Fire-fighting kit for HP 2.26 H pumpos with 2 fire hose connectors, 25 m fire hose, 5 m intake hose and fire lance.