



K12C5-ALIZE

PORTABLE POWER

GENERATING SET Range INDUSTRIAL

PRODUCT ADVANTAGES

- KOHLER water-cooled industrial engine
- Generating set guaranteed 3 years
- complete control panel
- Low noise level
- Large Autonomy

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range INDUSTRIAL

Leading edge technology, designed for regular, intensive use, that is powerful and quiet.



K12C5-ALIZE

GENERAL SPECIFICATIONS

| | |
|--|------------|
| Range | INDUSTRIAL |
| Frequency (Hz) | 50 Hz |
| Voltage (V) | 400/230 |
| Standard Control Panel | APM303 |
| Tank (L) | 50 |
| Sound power level guaranteed LwA dB(A) | 83 |
| Acoustic pressure level @1m in dB(A) | 67 |
| Acoustic pressure level @7m in dB(A) | 54 |

POWER

| Voltage (V) | ESP | | PRP | | Intensity (A) |
|-------------|-------|-------|-------|-------|---------------|
| | kWe * | kVA * | kWe * | kVA * | |
| 400/230 | 8,40 | 10,50 | 7,71 | 9,63 | 15 |

ENGINE SPECIFICATIONS

| | |
|---|------------|
| Engine brand | KOHLER KDI |
| Engine ref. | KDW1404 |
| Air inlet system | Atmo |
| Cylinders configuration | L |
| Number of cylinders | 4 |
| Displacement (l) | 1,37 |
| Bore (mm) | 75 |
| Stroke (mm) | 77,60 |
| Compression ratio | 22,8 : 1 |
| Speed (RPM) | 1500 |
| Pistons speed (m/s) | 3,88 |
| Maximum stand-by power at rated RPM (kW) | 11 |
| Frequency regulation, steady state (%) | +/- 2.5% |
| Governor type | Mechanical |
| Consumption @ 75% PRP load (l/h) * | 2,20 |
| Oil system capacity including filters (l) | 3,30 |
| Oil consumption 100% ESP 50Hz (l/h) | 0,06 |

ALTERNATOR SPECIFICATIONS

| | |
|--|----------|
| Alternator commercial brand | KOHLER |
| Alternator ref. | KH00350T |
| Voltage regulation at established rating (+/- %) | 1 |

PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 230V 16A socket - circuit breaker + 1 400V 32A socket - circuit breaker + Residual Current Device 30 mA + APM303

DIMENSIONS AND WEIGHT

| | |
|-----------------|-------|
| Length (cm) | 175 |
| Width (cm) | 77,50 |
| Height (cm) | 123 |
| Dry Weight (kg) | 340 |



23/07/2021

K12C5-ALIZE - PORTABLE POWER - GENERATING SET INDUSTRIAL

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com

KOHLER®

SDMO®

K12C5-ALIZE

ACCESSORIES SUPPLIED



User and maintenance manual

OPTIONS



CA308

ERR: not found in dict valeurs



VERSO-T

Automatic start up on lack of power (included engine preheating, battery charger, normal/back up reverser)



RMS

Commissioning : compliance checks of the installation, level controles, starting, no-load and load test, Instruction of the customer on the maintenance of the genset.

RAP

The adaptor for industrial sockets is used to connect 230-V appliances to the industrial socket.



RBH1

Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)



RBH0-5

Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).



RPM

Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V



RPQ

For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm² cable.

KOHLER®

SDMO®

23/07/2021

K12C5-ALIZE - PORTABLE POWER - GENERATING SET INDUSTRIAL

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com